

Cooling Technology

ZA-RT Motor Ball Valve Accessories

This extremely robust and reliable motor valve is the ideal control actuator for temperature control units in wineries and the beverage industry. It can be regarded as a high-end unit due to its solid design and high-quality material characteristics.

Features

- ▶ Valve body: stainless steel (1.4408)
- ▶ Operating voltage: 24 V/50 Hz; +/-10%
- ▶ Power input: 15 W / 30% ED / cos phi = 0,75
- ▶ Operating temperature: -10... +55 °C
- ▶ Media temperature: -20... +120 °C
- ▶ Adjustment time: 7... 13 s/90 °
- ▶ Protection rating: IP65
- ▶ Auxiliary limit switch: each 1U, 4... 230 V AC/DC; 10 mA... 5 A max
- ▶ Integrated emergency adjustment with position indicator
- ▶ Connection: DIN43650 socket (scope of delivery)

Designation	Details	Order no.	Unit price/€
ZA-RT-24-1/2"-VA	1/2", DN15	300.0130	
ZA-RT-24-3/4"-VA	3/4", DN20	300.0131	
ZA-RT-24-1"-VA	1", DN25	300.0132	

Please order the dirt trap separately
Larger models available on request



300,0130 to 300,0132

SF Brass/Stainless Steel Dirt Trap Accessories

Designation	Details	Order no.	Unit price/€
SF-1/2"-MS	1/2" DN15, brass with internal thread on both sides	304.0014	
SF-3/4"-MS	3/4" DN20, brass with internal thread on both sides	304.0015	
SF-1"-MS	1" DN25, brass with internal thread on both sides	304.0016	
SF-1 1/4"-MS	1 1/4" DN32, brass with internal thread on both sides	304.0017	
SF-1/2"-VA	1/2" DN15, stainless steel (1.4408) with internal thread on both sides	304.0250	
SF-3/4"-VA	3/4" DN20, stainless steel (1.4408) with internal thread on both sides	304.0251	
SF-1"-VA	1" DN25, stainless steel (1.4408) with internal thread on both sides	304.0252	
SF-1 1/4"-VA	1 1/4" DN32, stainless steel (1.4408) with internal thread on both sides	304.0253	

Larger models available on request



304,0014 to 304,0017



304,0250 to 304,0253

TSH Immersion Shaft Sleeve Accessories

Designation	Details	Order no.	Unit price/€
TSH-230-S	Immersion shaft sleeve 3/8" ET, M12x1.5mm IT, 1.4301, screw-in design	301.0006	
TSH-230-W	Immersion shaft sleeve, weldable, M12x1.5mm IT, 1.4301	301.0007	
TSH-230-HF	Immersion shaft sleeve, tapered wooden thread, M12x1.5mm IT, 1.4404	301.0029	
TSH-230-NW20-S	Immersion shaft sleeve NW20, M12x1.5mm IT, 1.4301, screw-in design	301.0030	
TSH-230-1/2"-S	Immersion shaft sleeve 1/2" ET, M12x1.5mm IT, 1.4301, screw-in design	301.0031	
TSH-230-ZLK	Mobile immersion shaft sleeve for bunghole valve M12x1.5mm IT, 1.4301	301.0033	
TSH-230-NW10-S	Immersion shaft sleeve NW10, M12x1.5mm IT, 1.4301, screw-in design *)	301.0034	
TSH-230-NW10/Clip-S	Immersion shaft sleeve NW10, M12x1.5mm IT, 1.4301, screw-in design	301.0035	

*) Only suitable for cable probe TF-5-8/15 or dial thermometer ZTM-80, not for Clip

